

characteristics ESD Unitec 2 with castors

Article: 9653E artificial leather

Dimensions in mm	Backrest:	H:	460
		Seat:	H: 440-590 B: 460 T: 470
	Packing data	Weight	kg 13,0
		Volume	m ³ 0,15



Base equipment

Benefit

Conductivity	The metal components have a conductive coating The high-comfort upholstery is also conductive Typical discharge resistance of 10 ⁶ Ohm Conductive castors	Exceeds the requirements of ESD protection according to standard DIN EN 61340-5-1 100% ESD protection
Backrest	Large, ergonomically designed backrest to take the strain off the spine and muscles with integrated lumbar support Backrest height adjustment convenient and easy to handle in sitting position	Healthy posture due to a hump providing support for the back in the lumbar region The support area can be adapted in accordance to the user's body size
Seat	Ergonomically designed seat with rounded front edge	The round front edge of the seat prevents blocked circulation in the thighs
Finishes for seat and backrest	ESD synthetic leather upholstery: High-level ESD synthetic leather Skai Tundra. Resistant to desinfectants, washable and easy-care Colour: black (2571)	The soft and comfortable upholstery provides a comfortable feel. However, damages caused by sharp parts can not be excluded Ideal for the use in production and laboratory
Seat height	Stepless seat height setting from 440-590 mm supported by safety gas spring with protective cover	Seat height can be adapted to nearly 95% of all body sizes, the cover protects the gas spring from dust and dirt
Functions / Mechanism	Permanent contact backrest Quick adjustment	This mechanism ensures that the backrest responds immediately to any movements of the upper body by following them. Thus, the back remains supported all the time The backrest can also be locked into any tilt position if required Every function can be operated comfortable and easy in sitting position
Base	Black 5 star base made from steel shape tube, conductive, powder-coated, black Flat design	Very high stability, longevity Flat design prevents stumbling hazard
Castors	Conductive Dual-wheel safety castors with load-sensitive brakes, for hard floors as standard	Chairs are braked when not used which decreases the accident risk
Materials	The materials used are recyclable	Environmentally friendly.
Standards	DIN EN European standard 61340-5-1 for ESD-protected areas DIN 68 877 German GS "safety tested" mark of confirmity Quality Management System DIN EN ISO 9001 Regulation EWG Nr. 1836/93 Environmental Management System DIN ISO 14001	100% ESD protection Procuring is insured
Warranty	10 year long term warranty, 3 years full warranty	Guaranteed quality and high efficiency

characteristics ESD Unitec 2 with castors

Article: 9653E artificial leather

Dimensions in mm	Backrest:	H:	460
		Seat:	440-590
	B:	460	
	T:	470	
Packing data	Weight	kg	13,0
	Volume	m ³	0,15



characteristics ESD Unitec 2 with castors

Article: 9653E artificial leather

Dimensions in mm	Backrest:	H:	460
		Seat:	H: 440-590
		B:	460
		T:	470
Packing data	Weight	kg	13,0
	Volume	m ³	0,15



Options		Benefit
Armrests	Loop armrest	Made of polyamide, adjustable in width (20 mm)
Accessories	Foot ring	The foot ring can be retrofitted by attaching it to the chair column